

SlowStop® Energy Absorbing Bollard – Type 2 (SS-T2Y-100)


www.slowstop.eu

Our workhorse model for distribution centers and general industry.
Recommended for fork lifts up to 5000 kg lift capacity.

Color: RAL 1023 Yellow Bollard on RAL 9005 Black Base

Diameter: 101,6mm (6,3 mm wall)

Height: 100 cm

Set Screws: 5 M16 x 2,00
8mm Hex

Cap: Black Plastic

Installs with four (4)
Concrete Anchor Screws



MASS (KG)	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	15000
SPEED (KPH)											
3.0											
3.5											
4.0											
4.5											
5.0											
5.5											
6.0											
6.5											
7.0											
7.5											
8.0											
8.5											
9.0											
9.5											

No Damage / Negligible Damage
Will Stop / Potential Damage to Guard
Guard is under-sized



SPECIFICATIONS

- Stopping Power Rating: 5.334 joules | 62.7 kN
- Temperature Rating: -40° to 70°C
- Pipe Coating: EN-ISO 1461 Galvanized + Polyester Powder Coat
- Base Coating: Environmentally Friendly Water-Based KTL Coating + Polyester Powder Coat. C5I corrosion resistance.
- Frangible base eliminates floor damage. Safe for structural concrete.

RECOMMENDED USES



- Powered Industrial Trucks to 5000 kg lift capacity
- Equipment and Storage Rack Guarding
- Door and Wall Protection
- Utility Protection
- Pedestrian Safety
- Parking Facilities
- Fuel Pump Protection
- Not for Hostile Vehicle Security



4955 Stout Dr. • San Antonio, TX 78219
TEL: +1 (210) 736 4477 • FAX: +1 (210) 734 6448
Email: info@slowstop.eu
www.slowstop.eu



QR: Download Spec Sheets
©2020 SlowStop. All rights reserved. 10-FEB-2020