

SlowStop® Energy Absorbing Bollard – Type 3 (SS-T3Y-100)



The strongest surface mount bollard available. For maximum protection in the most difficult applications.

Color: RAL 1023 Yellow Bollard on RAL 9005 Black Base

Diameter: 177,8 mm (8 mm wall)

Height: 100 cm

Set Screws: 8 M16 x 2,00
8mm Hex

Cap: Black Plastic

Installs with eight (8)
Concrete Screw Anchors



SPECIFICATIONS

- Stopping Power Rating: 25.800 joules | 147.3 kN
- Temperature Rating: -40° to 70°C
- Pipe Coating: EN-ISO 1461 Galvanized + Polyester Powder Coat
- Base Coating: Environmentally Friendly Water-Based KTL Coating + Polyester Powder Coat. C5I corrosion resistance.
- Frangible base eliminates floor damage. Safe for structural concrete.

RECOMMENDED USES

- Loading Docks and Warehouse Entrance Ramps
- Equipment Guarding
- Wall and Door Protection
- Utility Protection
- Pedestrian Safety
- Fuel Pump Protection
- Storage Tanks
- Not for Hostile Vehicle Security



4955 Stout Dr. • San Antonio, TX 78219
TEL: +1 (210) 736 4477 • FAX: +1 (210) 734 6448
Email: info@slowstop.eu
www.slowstop.eu



QR: Download Spec Sheets
©2020 SlowStop. All rights reserved. 10-FEB-2020