SURFACE MOUNT H.V.M CRASH GATE-40 IWA 14 Crash Tested to Stop a 7.2 Tonne Truck Travelling at 40mph/64km/h at 90°



No Pinning to the surface H.V.M install in 2 hours



Benefits

- Install time 2-3 hours
- NO Mains Electricity needed
- NO Pinning to the surface
- NO Floor Rebating
- NO Need to install on Flat Ground
- The System sits on Top of the Ground
- Can be used for Temporary Events or Permanent Install



Secure, reliable and highly effective...

The Safetyflex design team have responded to clients' requirement for a new type of surface mount gate that can be installed within 2-3 hours, with no man handling to operate the gate, and the gate to open horizontally to save ground space.



HOME OFFICE

Patent Applied For

DESIGNED TO STOP A CAR AND TRUCK WITH ONE FRONT GATE



NO MAINS POWER NEEDED OPERATES WITH A 18 VOLT CORDLESS DRILL

Secure, reliable and highly effective...

This brand new surface mount gate developed by the Safetyflex design team gives instant HVM protection and the ability to close off roads within hours.

The new unique Crash Gate 40 system was crash tested at Horiba-Mira crash centre to IWA-14-1 vehicle impact test with a 7.5 tonne truck at 40mph/64km/h at 90 degrees and stops the vehicle in 3.7 metres.

There is no man handling needed to open the gate. Just unlock the gate locking bolt on the right hand post and use an 18v cordless drill to drive up the barrier from the hydraulic pump located on the left-hand post of the gate. To lock the gate, simply put the drill in reverse and this will drive the barrier back down.





Safetyflex Barriers Boston Place, Coventry UK CV6 5NN UK Sales Tel: +44 (0) 2476 662116



email: info@safetyflexbarriers.com email: us@safetyflexbarriers.com

www.safetyflexbarriers.com